Dual Regulated Power Supply for Control B pre-amplifier



Our new amplifier Control B is a surprising quality fitting, its low price and its little size could let think that it is an ordinary apparatus, we thought that it was necessary to give it more prestigious features by reinforcing its power supply device.

Now the "control B" is available with the "Dual regulated power supply".

That power supply totally electronically regulated, includes 3 tubes, 1 rectifier 5Y3 provides the direct current to the regulation device constituted by a low internal impedance tetrode 6Y6 working with a sharp cut off pentode EF 184 which issues the amplification of the error signal.

The whole fitting allows maintaining the power supply of the preamplifier perfectly constant even if the main voltage varied between 170 V and 260 V.

The power supply is hold in a 2 mm steel sheet housing ventilation holes widely provided with.

The front plate calling to mind the look of "control B" is constituted by a 10 mm champagne coloured aluminium plate finely burnished and brushed.

Power Supply	230V/50Hz – 117V/60Hz
Power Consumption	30 Watts
High Voltage Output	320V – 30 mA
Low Voltage Output	18V – 0A6



5/7 rue d'Ormesson 93800 Epinay sur Seine - FRANCE Phone : (33) 1 48 41 89 74 Fax : (33) 1 48 41 69 28

Web: http://www.jcverdier.com Email: jcverdier@jcverdier.com High-End Turntables & Vacuum Tubes Amplifiers